FAMILY-RUN OAK SAWMILL · 20+ YEARS

Oak sawn at the source.

Wood World Trading is a family-run sawmill in Serbia. We cut, dry and grade European Oak, *Quercus robur* and *Quercus petraea*, for furniture makers, flooring and joinery manufacturers, and importers worldwide.



YEARS SAWING OAK	OAK LOGS CUT PER YEAR	KILN-DRYING CAPACITY	PEOPLE AT THE MILL
20+	10,000 m³+	2,000 m³	50+

WHY BUYERS WORK WITH US

Consistency

Every bundle is graded by the same team to the same standard. What you approve on the first order is what you receive on the tenth.

Stability

A steady supply you can plan around. Agree a volume per month and we deliver it, month after month.

Reliability

A family business that has supplied Oak for more than 20 years. Clear specifications, honest grading, delivered as agreed.

Mill-direct prices

You buy from the sawmill itself. No traders in between, no added margins.

Responsibly sourced from managed forests EUDR and UKTR compliant We ship worldwide

GRADE

UWP

Ultra-wide prime boards.

Super-Prime quality in extra-wide boards, 230 to 450 mm. No sapwood, practically no knots, wide clean faces.









PHOTOS OF OUR STOCK

CLOSEST EQUIVALENT **QF1a · AA**

Width	230 to 450 mm
Clear faces	Three to four
Sapwood	None
Knots	Practically knot-free. Occasional pin knots up to 10 mm only.
Heart	Not allowed
Worm holes	Not allowed
Cracks	Occasional surface cracks on one face. End cracks up to 100 mm.
Straightness	Max. 5 mm side bend per metre
Typical use	Table tops, stair treads, wide panels, wide-plank flooring.
Thickness	26 · 32 · 38 · 50 mm
Drying	Kiln-dried to 8–12% moisture, or fresh sawn

GRADE

Super-Prime

Clear on up to four faces.

Square-edged boards clear of knots and sapwood on three to four faces. Virtually defect-free.









PHOTOS OF OUR STOCK

CLOSEST EQUIVALENT **QF1a · AA**

Clear faces	Three to four
Sapwood	None
Knots	Practically knot-free. Occasional pin knots up to 10 mm only.
Heart	Not allowed
Worm holes	Not allowed
Cracks	Occasional surface cracks on one face. End cracks up to 100 mm.
Straightness	Max. 5 mm side bend per metre
Typical use	Staircases, fine furniture, windows and doors, visible joinery.
Thickness	26 · 32 · 38 · 50 mm
Drying	Kiln-dried to 8–12% moisture, or fresh sawn

GRADE

AB

A prime face, allowances on the back.

At least one face fully clear of knots and sapwood. Minor knots and sapwood allowed on the reverse.









PHOTOS OF OUR STOCK

CLOSEST EQUIVALENT **QF1a X · UK Prime**

Clear faces	At least one, fully clear of knots and sapwood
Sapwood	None on the clear face. Minor sapwood on the reverse.
Knots	None on the clear face. Minor knots on the reverse.
Heart	Not allowed
Worm holes	Not allowed
Cracks	Occasional surface cracks on one face. End cracks up to 100 mm.
Straightness	Max. 5 mm side bend per metre
Typical use	Tables, flooring, cladding, mouldings, furniture fronts.
Thickness	26 · 32 · 38 · 50 mm
Drying	Kiln-dried to 8–12% moisture, or fresh sawn

GRADE

FAS

A balanced mix of Prime, AB, and Joinery.

Mostly clear faces with some small knots and sapwood. Good yield at a lower price than AB.









PHOTOS OF OUR STOCK

CLOSEST EQUIVALENT

NHLA FAS · Mix of Prime, AB, and Joinery

Clear faces	Mostly clear
Sapwood	Some, max. 25% of board width
Knots	Some small sound knots
Dead knots	Small, limited
Heart	Not allowed
Worm holes	Not allowed
Cracks	Occasional surface cracks. End cracks up to 100 mm.
Straightness	Max. 5 mm side bend per metre
Typical use	Furniture components, joinery, flooring, cabinetry.
Thickness	26 · 32 · 38 · 50 mm
Drying	Kiln-dried to 8–12% moisture, or fresh sawn

GRADE

Joinery

The all-round grade of European Oak.

Sound boards with more small knots and some sapwood allowed. Dependable for windows, doors, stairs and furniture.



ILLUSTRATION

CLOSEST EQUIVALENT QF2

Clear faces	Not required
Sapwood	Some, max. 30% of board width
Knots	Small sound knots allowed, up to 40 mm
Dead knots	Small dead knots allowed
Heart	Traces allowed if they can be machined out
Worm holes	Max. one per running metre
Cracks	Occasional surface cracks on both faces. End cracks up to 100 mm.
Straightness	Max. 5 mm side bend per metre
Typical use	Windows, doors, stairs and furniture.
Thickness	26 · 32 · 38 · 50 mm
Drying	Kiln-dried to 8-12% moisture, or fresh sawn

GRADE

BC

Character Oak.

Knots are part of the look. A cutting grade for shorter clear parts and rustic full-length pieces.







PHOTOS OF OUR STOCK

CLOSEST EQUIVALENT **NHLA No. 1 Common**

Clear faces	Not required
Sapwood	Allowed, but no face fully sapwood
Knots	Unlimited, up to 40 mm
Dead knots	Allowed. No open knots over 40 mm.
Heart	Allowed
Worm holes	Max. one per board
Straightness	Max. 10 mm side bend per metre
Typical use	Shorter clear parts, rustic furniture and flooring, full-length rustic pieces.

Thickness	26 · 32 · 38 · 50 mm
Drying	Kiln-dried to 8–12% moisture, or fresh sawn

SIZES AND DRYING · EVERY GRADE



26 mm | 32 mm | 38 mm | 50 mm

END-VIEWS TO SCALE · BOARD WIDTH SHOWN 140 MM

Species	*Quercus robur*, *Quercus petraea*
Thickness	26 · 32 · 38 · 50 mm
Width	Random widths, as each log yields them. Need fixed widths? We cut to your specification on request.
Length	From 500 mm. Longer lengths on request.
Drying	Kiln-dried to 8-12% moisture, or fresh sawn

GRADES AT A GLANCE

GRADE	CLEAR FACES	SAPWOOD	KNOTS	CLOSEST EQUIVALENT
UWP	Three to four	None	Practically knot-free. Occasional pin knots up to 10 mm only.	QF1a · AA
Super-Prime	Three to four	None	Practically knot-free. Occasional pin knots up to 10 mm only.	QF1a · AA
AB	At least one, fully clear of knots and sapwood	None on the clear face. Minor sapwood on the reverse.	None on the clear face. Minor knots on the reverse.	QF1a X · UK Prime
FAS	Mostly clear	Some, max. 25% of board width	Some small sound knots	NHLA FAS · Mix of Prime, AB, and Joinery
Joinery	Not required	Some, max. 30% of board width	Small sound knots allowed, up to 40 mm	QF2
BC	Not required	Allowed, but no face fully sapwood	Unlimited, up to 40 mm	NHLA No. 1 Common

REQUEST A QUOTE

Tell us what you need.

Grade, thickness, length and volume are enough to start. We reply with availability and a price, direct from the mill.

f.chami@wwt.rs

wwt.rs

WWT DOO SR.MITROVICA
Višnjevačka 1, 22000 Sremska Mitrovica, Serbia
Reg. no. 08795274